

12/3 Extension Cords

Our 12/3 Outdoor Extension Cords are tailored specifically for the event rental industry and feature a high visibility CENFLEX™ P.V.C. jacket that withstands rough use, chemicals, moisture, and ozone and provides added flexibility at below freezing temperatures. The molded-on non-slip plugs, available in single tap and triple tap, resist breaking or pulling off. Our white cords are best suited for applications with light backdrops such as white tent tops, sidewalls and white pole covers. For dark backdrops, such as pavement or grass, our 25' black single tap cord is ideal. The 10' molded on triple tap cord is a perfect power source for lighting clusters affixed to center poles. All of our extension cords are U.L. Listed and meet OSHA requirements. See the table below for a complete listing of our single and triple tap extension cord selection.

Now Available in 25'!



Description	Product Code
25' White 12/3 Single Tap	D14512025
50' White 12/3 Single Tap	D14512050
100' White 12/3 Single Tap	D14512100
10' White 12/3 W/Trip Tap	D15613010
25' Black 12/3 Single Tap	D16624025



Durable Pro Cap™ Outlet Covers Keep Dirt and Moisture Out.

50' White Multi Outlet Cord

Our 50' White 12/3 Multi Outlet Extension Cord features six outlets with Pro Cap™ covers to keep dirt and moisture out of unused sockets.

Features:

- 15A-125V
- 50', Six Outlets
- -40F Coldweather Jacket
- U.L. Listed

Description	Product Code
50' White 12/3 Multi Outlet Ext. Cord	D12420050

White Triple Tap Adapter

Features:

- Convert any heavy duty Ext. Cord into a 3-Outlet Cord-Set
- Abrasion resistant P.V.C. Molded Shell
- 15A-125V
- U.L. Listed

Description	Product Code
White Triple Tap Adapter	D10100002



Electrical

25' Triple Tap Generator Cord

This 10/3 cord is built for the most rugged of applications and is perfect for use with our Wacker 5600W Portable Generator.

Features:

- 15A-125V Connector
- Lighted Triple Tap End
- -40F Coldweather Jacket
- Water & Flame Resistant



Description	Product Code
25' Black 10/3 Generator Cord	D13010025

WACKER

Rugged and Powerful Generators for the most demanding job sites!

Free Shipping on
all Wacker Brand Products
Anywhere in the cont. US!



Wacker 2,500W 5.5HP Generator

- Maximum output 2,500 W
- Continuous AC amps 18.8 A
- Voltage AC 120 V
- 1-125V, 20 A Duplex W/GFCI; 1-125V, 20 A Duplex
- 5.5 HP Honda Recoil Start
- 4.5 Gallon Fuel Capacity
- 10.5 Hours Run Time at Full Load
- 73 DBA Noise Level
- 1 Year Warranty
- Shipping Weight 104 lbs.

GV2500A

Wacker 5,600W 11HP Generator

- Maximum output 5,600 W
- Continuous AC amps 20.8 A
- Voltage AC 120/240 V
- 2-125V, 20 A , 1-125V, 30 A Twist Lock;
1-125/250V, 30 A Twist Lock
- 11HP Honda Recoil Start
- 7.4 Gallon Fuel Capacity
- 9 Hours Run Time at Full Load
- 81 DBA Noise Level
- 1 Year Warranty
- Shipping Weight 179 lbs.

GV5600A



*Special CARB version required for use in California, please call for CARB Generator pricing and availability.

**Free shipping on Wacker products in Cont. U.S. only. Residential and/or liftgate surcharge may apply. Unless provided with a Tax Exempt Cert., sales tax may apply to Wacker products in certain states.



50' Cage Light Set

Our Cage Light Sets are durable enough for use in work and construction areas, yet aesthetically pleasing enough for use to illuminate tents and event areas. The set includes convenient metal hooks for hanging and attachable white vinyl cages for bulb protection.

Features:

- Heavy Duty White 12/3 600V Cord
- Sockets Spaced every 10'
- Molded on Weatherproof Lamp Holders
- Vinyl Cages and Metal Hooks Included
- Rated for up to 200W Bulbs (not included)
- U.L. Listed, cUL Approved (Canada), Meets OSHA Specs.

D12022050

G.F.C.I. In-line Shock Protector™

With Lighted Triple Tap End!

Features:

- Triple tap features Primelight™ power indicator light
- 3ft. 12/3 SJTW power cord has in-line G.F.C.I. for shock protection
- Rated for up to 15 Amps or 1,875 Watts
- Ultra flexible up to -40 Degrees F.
- U.L. Listed and meets all OSHA requirements



Description	Product Code
3' Inline G.F.C.I.	GF320803

**G.F.C.I. Surge Protectors are recommended for all outdoor lighting/electrical applications.*



Stage 4 Dimmer

Features:

- 1,650-watt sound activated controller with individual fader controls
- 16 built-in automatic and sound-activated chases
- Full on and blackout
- Speed control
- 4 individually-fused AC outlets on rear
- 4 dimmer faders for manual control/override
- Output (115V): 5A (400W) per channel
- AC power: Switchable 115V/230V 50/60Hz
- Weight: 5 lbs.
- Size: 11" X 4.5" X 2.8"

Description	Product Code
Stage 4 Dimmer	TFX-DC4

A Must Have for any Field Lighting Kit!

P.V.C. Electrical Tape

¾" × 60' U.L. & C.S.A. Listed

PVCT/COLOR

**Minimum order five (5). Colors available include Blue, Red, Yellow, Black & White.*

